



YHY638FU Manual

Ordering Information	
Model No.	YHY638FU
Name	Multiple RFID Read/Writer
Phone	86-010-80128328
Email	info@ehuoyan.com
Web	http://www.ehuoyan.com/

1. Overview

The YHY638FU multiple RFID reader writer is a PC-linked contactless smart card reader/writer developed based on the 13.56 MHz Contactless (RFID) Technology. It supports MIFARE®1k, MIFARE®4k, MIFARE Ultralight®, NTAG203, NTAG213, NTAG215, NTAG216 and ISO 14443A compatible cards.

YHY638FU use USB port to act as a virtual COM port. The proximity operating distance of YHY638FU is up to 6 cm, depending on the type of contactless tag in use.

The YHY638FU is ideal for secure personal identity verification, access control, e-payment, e-ticketing for events and mass transit, toll road fare collection and network authentication.

It support these cards:

- ▲.ISO 14443 A: Mifare_One(S50&S70)/UltraLight/, NTAG213,NTAG216
- ▲.ISO 14443B: AT88RF020/SR176/SRIX4K
- ▲.ISO 15693:Tag_it (2k) HF-1/I.CODE SLI

2. Special Features

- Support ISO 14443 A, 14443B, 15693
- RF Frequency: 13.56 MHz.
- Typical time of command: <100ms
- Operating distance: up to 6 cm
- Communications Interface: USB
- Two LED indicators (software controlled)
- Buzzer alarm (software controlled)
- Mechanic characteristics:
 - Size: 110 x80x 26 (mm)
 - Cable length: 1.5m
 - Weight: 200g (include USB cable)

3. Technical Specifications

Dimensions	110 mm (L) x 80 mm (W) x 26 mm (H)
------------	------------------------------------

Weight	200 g (including USB cable)
Cable length	1.5m
Color	Black
Interface	USB (VCP)
Baud rate	115200 bps (default)
Operating Distance	Up to 6 cm (depends on the tag type)
Supply Voltage	5V DC (USB power)
Supply Current	80mA (operating); 110mA (maximum)
Operating Temperature	-10~50 °C
Storage Temperature	-20~70 °C
Operating Frequency	13.56 MHz
RF Speed	212 kbps
Smart Card Supported	MIFARE [®] 1k, MIFARE [®] 4k, NTAG213,NTAG216, ICODE SLI
Operating System	Win NT, Win 2k, Win XP, Win Vista, Win 7, Win10, Linux

4. Typical Applications

- ✓ E-Payment
- ✓ E-Healthcare
- ✓ E-Game
- ✓ E-Government
- ✓ E-Ticketing
- ✓ Access Control
- ✓ Network Login
- ✓ Transportation
- ✓ Loyalty Program

5. How to use

Step1: Open the folder “USB_Driver_Windows”, then you will find two installer programs shown as below.


名称	修改日期	类型	大小
SLAB_License_Agreement_VCP_Windo...	2013/3/6 16:13	Text file	9 KB
CP210xVCPInstaller_x64	2013/3/6 16:13	应用程序	655 KB
CP210xVCPInstaller_x86	2013/3/6 16:13	应用程序	533 KB
dpinst	2013/3/6 16:13	XML 文档	12 KB
ReleaseNotes	2013/3/6 16:13	Text file	10 KB
slabvcp	2013/3/6 16:13	安全目录	11 KB
slabvcp	2013/3/6 16:13	安装信息	5 KB
x64	2013/3/6 16:13	文件夹	
x86	2013/3/6 16:13	文件夹	

If the user's OS is **windows 32 bits**, then click "CP210xVCPInstaller_x86.exe" to install the driver, else **if 64 bits**, then click "CP210xVCPInstaller_x64.exe" to install the USB driver. (Note: if you have installed the driver before, then go to step2).


Step2: On the next picture, please click "next step".



Step3: On the next picture, select "I accept this agreement", next click "next step".



Step4: On the next picture, click “Finish”, then the USB driver install fully.



Step5: Connect the YHY638FU to the USB port of PC, shown as below.



After power on the RED led will flash one time, then the buzzer will beep one time, at last the blue led will light on, it means that the reader is ready now. You can send the commands from the host to the YHY638FU.

After connect the USB, you can see the Virtual Com Port (VCP) on the “Device Manager”.

How to find out which communications port the operating system has assigned to the USB driver?

Windows XP---


The path is:

Start=>Control Panel=>System(you might need to set your Control Panel to 'Classic View')=>Hardware=>Device Manager=>Ports(COM & LPT)

Vista and Windows 7---

The path is:

Start=>Control Panel=>Device Manager(you might need to set your Control Panel to 'Classic View')=>Ports(COM & LPT)




Note: If the COMX exceed COM10, please change it between 1 to 9, for example, it shows COM12, then you can change it into COM3.


HOW TO CHANGE COM PORT NUMBER?

If you need to change the port number assigned to your USB driver, proceed to next step to change the USB driver port number in the Device Manager.

1) Right click on the selected COM port and select "Properties".




2) Open the "Port settings" tab and select "Advanced".



- 3) In the “Advanced Settings” window, activate the drop-down for “COM Port Number” you will be presented with a list of ports. Click on an unused port to change the COM port for your USB driver. Click “OK” to close the “Advanced Settings”, then the “Properties Windows”. Close the “Device Manager” windows then **RECONNECT** the USB and re-open the “Device Manager”, your USB driver should now be assigned to the new port.

Note: Even if the COM port shown “in used”, but in fact there is no such a device connecting to your PC, then you can select it.



Step6: Now, you can run the program to send commands to the YHY638FU. You can run the eReader.exe or else App(base on the dll files) to communicate with the YHY638FU. The YHY638FU will not do anything unless you send command to it. There is only one program can be run and connect to the YHY638FU at the same time.

Note: For the eReader program please reference the eReader manual.

6. Troubleshooting

No.	fault	solution
1	No sound when power on	If the led is not light, plug the USB again or plug it into another USB port.
2	Blue led not light when power on	Same with above.
3	Beep all the time when power on	Reconnect the USB.
4	Can not read the card	Click "Device->Connect", If connect ok, then

		the card maybe bad or is not a mifare card, or you maybe put the reader on the metal surface.
5	Can read card SN, but can not read or write the blocks	You have not the right authenticated keys.

Contact Information:

EHUOYAN Technology Co., Ltd.

Tel: +86 -010-80128328

Email: info@ehuoyan.com

Web Site: www.ehuoyan.com